

Using the TimeSavers ~explorer shortcut to create links launching Windows Explorer

- **alert ~explorer (.)** [Link](#)

Starts Windows Explorer, displaying the folder that was opened last in Acrobat (when File > Open was used).

If the PDF was opened through double-clicking, the default folder shown when clicking this link is the Adobe Acrobat folder.

- **alert ~explorer (c:\\temp)** [Link](#)

Starts Windows Explorer with the specified folder opened (system-dependent). Note the use of a double backslash as a folder separator. Using a single forward slash as a folder separator results in an error (“path does not exist or is not a directory”); a single backslash may be treated as a prefix used to specify FrameMaker control characters.

- **alert ~explorer ()** [Link](#)

On Windows 2000/XP, starts Windows Explorer with My Computer open (a space between the parentheses).

- **alert ~explorer ()** [Link](#)

On Windows 2000/XP, starts Windows Explorer with the My Documents folder open (no space between the parentheses).

- **alert ~explorer (/n)** [Link](#)

Starts Windows Explorer window using the default setting. On Windows 2000/XP, this is usually the root of the drive on which Windows is installed.

- **alert ~explorer (/select, C:\\temp.mif)** [Link](#)

Windows 2000/XP: Starts Windows Explorer with C:\\temp.mif file selected. Note the comma after /select.